



## Certificate of Analysis

GeoEngineers, Inc., an independent materials testing facility, has witnessed these tests on a production batch of StreetBond SR. This material is known to have been produced by an ISO9001:2000 certified coatings manufacturing facility. GeoEngineers confirms that the results of the testing were as follows:

<b>Testing of StreetBond SR</b>		
Test Method	Parameters	Measured result
<b>ASTM D 4060</b> Taber abrasion resistance	1 day cure, H-10 wheel: cycles (dry)	0.97 g/1000
<b>ASTM D 570</b> Water sensitivity	Water absorption after 9 days exposure: Remaining absorption after 1 hour of recovery:	8.3% 0.4%
<b>ASTM D 522-93A</b> Flexibility as measured by Mandrel bend	0.5mm thick sample passes 6.35mm at 21°C 0.5mm thick sample passes 101.6mm at -18°C	
<b>ASTM G 155</b> Color stability	Xenon Arc - 2000 hrs (CIE Units)	Brick $\Delta E=0.49$
<b>ASTM D 2486 Modified</b> MEK Scrubs	16 dry Mills, Number of Scrubs until 50% substrate exposed.	>5000
<b>EPA 24</b> <b>ASTM D 3960-05</b> Volatile Organic Compounds	Water-based Acrylic	VOC 18.7 g/l
<b>ASTM E 303</b> Surface Frictional Properties Using the British Pendulum Tester	14-Day Cure Coverage 150 sq ft per Pail Temperature Tested: 96°F-99°F	94 BPN

This certificate confirms that the above product was tested as per stated standard specification using calibrated equipment and qualified staff.

Signed:   
 Timothy D. Barber  
 Senior Technical Manager  
 A2LA certificate 1670.01

Signed:   
 James B. Harakas  
 Professional Engineer

Date: 3/1/2010

Date: 03/01/10

File No. 9688-001-04

